



BOBCAT S250 SKID STEER LOADER

Bobcat s250 skid steer loader

Standard Equipment

Adjustable cushion seat
Alarm package
Automatically activated air intake heater
Auxiliary hydraulics: variable flow/maximum flow
Bob-tach
Bobcat interlock control system (bics™)
Deluxe operator cab* includes: interior cab foam, top & rear windows,
Accessory wire harness, dome light and electrical power port
Engine/hydraulic systems shutdown
Hydraulic bucket positioning
Instrumentation: hourmeter, engine temperature and fuel gauges and warning lights
Lift arm support
Lift path: vertical
Lights, front and rear
Two (2) 74" buckets one (1) with teeth
Parking brake
Seat bar
Seat belt
Suspension seat
Spark arrestor muffler
Tires: 12-16.5, 12 Ply rating, bobcat severe duty with two (2) spare assemblies
Turbo charger
Roll over protective structure (rops) – meets requirements of sae-j1040 & iso 3471
Falling objects protective structure (fops) – meets requirements of sae-j1043 & iso3449, level i
(Level ii fops is available – see under dealer installed accessories – order from parts)


Quick specs

| | |
|-----------------------------|--|
| Rated operating capacity | 2500 lbs. |
| Engine make/model | kubota/v3300-di |
| Engine fuel/cooling | diesel/liquid |
| Horsepower (sae net) | 75 |
| Displacement | 202.53 Cu. In. |
| Auxiliary hydraulics flow | 20.7 Gpm 20.7 Gpm |
| Travel speed | 7.2 Mph |
| Operating weight | 7674 lbs. |
| Shipping weight | 6877 lbs. |
| Cab height | 80.9 In. |
| Width (without attachment) | 72.0 In. |
| Length (without attachment) | 114.1 In. |
| Wheelbase | 48.8 In. |
| Reach @ maximum height | 34.0 In. |
| Height to hinge pin | 126.4 In. |



ONE STANDARD FLOW (1) BOBCAT 14" PLANER

Ship Weight..... 1520 lbs.
Operating Weight..... 1460 lbs.
Drum Width..... 14"
Cutting Depth-Flat Planing..... 0 – 6"
Sideshift..... 26"
of Bits..... 46



BOBCAT 72" SWEEPER

Shipping Weight 910 lbs.
Operating Weight845 lbs.
Sweep Width.....72"
Overall Attachment Width.....78.2"
Bucket Capacity.....14.4 cu. ft.
Broom Diameter 21.4"
Bristle Sections (Included) 36
Bristle Material Replaceable Polypropylene sections (steel sections avail.)
Cutting Edge (Repl. Steel)......5/8" x 6"
Broom RPM @ 10 GPM145
Travel.....Frwd/Rev

