



TRAILERS

Etnyre Transport Trailer

Etnyre Transport Trailer

Model	Steel-Bituminous
Tank Construction	Model LWR
Capacity	6500 US Gallons
Outage	1% (Minimum)
Code	49 CFR 173.247
Design Pressure	Atmospheric
Venting	Asphalt Type
Temperature Rating	500 Degree F
Material (Barrel)	Carbon Steel-10 Gauge
Surge Plates	Two- 10 Gauge
Compartments	One
Capacity Markers	2-disc
Insulation	3" Fiberglass-1# density
Aluminum Jacket	.040" Side Sheets/ .080" Heads
Rear Discharge Valve	6" Valve w/ 3" Line & Camlock Cap
Thermometer	2" Dial in well with Plexiglass cover
Manhole	20" Asphalt type
Manhole Platform	4-sided, Open grate- steel
Manhole Overflow	3" Internal
Heating System	(1) 8" x 6" with S.S. Stack (No Burner)
Ladder	Steel-Curbside
Walkway	None
Hose Trough	20' Aluminum, Curbside
Tire Carrier	Basket Type
Fenders Fenders	Aluminum, Front & Rear (with Mudflaps on Rear)
Lights	LED Type with S.S. Light boxes at rear
Glad Hands	Low Mount



Steel Bumper- Split Type	Incorporates sloping outlet
Conspicuity Tape	Per DOT Requirements
Upper Coupler	Bolted and Adjustable
Landing Legs	2-speed, Curbside Crank
Suspension	Reyco 21-B Tandem, 9-leaf spring
Oil Seals	Stemco
Air Brakes	16.5" x 7" w/ Auto Slacks
Anti-Lock Brakes	2S/2M System (2 Sensors/ 2 Modulators)
Axles	(2) 22,500# beam rating each
Steel Disc Wheels	(8) 10-hole, Hub Piloted
Tires	(8) 11R22.5-H (16 ply) Yokohama
Paint	Steel Parts only-Black
Placard Kit	Flip Type, 4-sides
Sample Valve	¾"
Tool Box fender	6" x 10" x 30" Steel with hinged lid, mounted on

