

McNeilus 10 Yard Concrete Mixer

McNeilus 10 Yard Concrete Mixer

CHASSIS:

Sterling Make:

MBE4000-450 12.8L, 450HP @ 1,900 RPM, 1,550 LB/FT @ 1,000 RPM Engine:

Eaton Fuller RTO-16909 ALL Transmission:

Front Axle: MFS-20-133A 20,000 LBS

Rear Axle: RT-46-160P R-Series Tandem, 46,000 LBS

Tuftrac 46,000 LB 2 Stage Rear Spring

Wabco 4S/4M ABS

McNeilus Body Features:

*Mixer Type		
STD	Base Body	Standard Mixer
Charge Hopper	r	
STD	Hopper Style	Standard
Chute	-	
MANUAL	Chute Swing	Manual
STSTD	Extension, First	Standard, steel
STSTD	Extension, Second	Standard, steel
STD	Foldover	Standard Foldover Handle
MANUAL	Foldover	Manual Operation
TRANS	Foldover	Transitional
MAN	Lock	Manual lock
5	Main	5 ft Main Chute
STD	Miscellaneous	Standard Clevis
FENDERD1	Rack, Extn (First)	Fender mount, driver side (1)
FENDERP	Rack, Extn (Second)	Fender mount, passenger side
STITCHED	Weld, Extensions	Stitched
STITCHED	Weld, Foldover	Stitched
STITCHED	Weld, Main	Stitched

Collector

RUBBER	Bib	Rubber
STD	Style	Standard

Controls, Mixer

BOX	Cab Configuration	Box
CABLE	Drum	Cable
Υ	Drum	Remote Drum Start/Stop



	Capacity	10yards
42	Discharge Opening	42*
1/4	Fins	1/4" (nominal)
BOLTED	Fins, Surge	Bolted
1	Hatch, Bolted	One (1)
1/4	Head	1/4" (nominal)
STD	Profile	Standard
1/4	Skin	1/4* (nominal) Skin Thickness
STD	Tail Cone	3/16 inch thickness nominal
STD	Transmission	Standard Lube
P7300	Transmission	ZF P7300
STEEL	Туре	Steel Drum

Fenders

STD	Mudflaps, Brackets	Standard
WPL	Mudflaps, Front	White plastic
WPL	Mudflaps, Rear	White plastic
N	Overlap	No
STEEL	Rear	Steel Skin
STS	Rear Supports	Steel, straight
96	Rear Width	96" width over fenders

Hydraulics

5.4	Motor	5.4 cubic inch Eaton
STD	PTO Shaft	Standard
5.4	Pump, Main	5.4 cubic inch Eaton
STLRD	Reservoir	Round, steel
PEDF	Reservoir Location	Pedestal, front

Lighting

INC	*Lighting Type	Incandescent
STD	Backup Alarm	Standard 12-36V alarm
STT	Fenders, Rear	Stop/Tail/Turn
CHOP	ICC Three Bar	On charge hopper



NONE	License Plate	No License Plate Light	
Miscellaneou	ıs	•	
ENG/SP	Decals	English / Spanish	
Paint	•	-	
TEMP	Category	Standard template	
1L	Configuration	One color, low complexity	
Pedestal, Fro	ont	·	
STD	Pedestal Style	Standard	
1/4	Thickness	1/4" (nominal)	

Knee Braces

Wide 1/4" (nominal)

Water System

WIDE

Pedestal, Rear

Bracing

Thickness

Ladder Platform

There by the same of the same				
SINGLE	Nozzles, Injection	Single	Т	
CAST	Tee, Injection	Cast		
SBV	Valves, Injection	Standard ball valves	П	
BALL	Washout, Lower	Ball Valve	٦	
STD	Water Line Routing	Standard	Т	
	Water Tank 1	125 gallons, steel	П	
TOPSTD	Water Tank 1 Fill	Top fill		
SIDEMTD	Water Tank 1 Location	Side mount, driver side	Ī	

