



ISUZU CYZ51N-06 DUMP TRUCK

ISUZU CYZ51N-06 DUMP TRUCK

SPECIFICATIONS

Engine: Model 4 cycle, direct injection, water cooled, in-line, OHC Intercooler turbo Charger

Cylinders: 6

Bore x stroke (mm): 147 x 140

Displacement (cc): 14,256

Compression ratio (to 1): 17.0

Max output ISO (gross): 265kw, 360ps / 1800rpm

Air cleaner: Single paper element with Cyclone-Donaldson 13"

Transmission: 7 speed

Brakes: Full Air

Wheels & Tires: Disc wheel: 20 x 7.50V (10 studs)

Tire (STD): 11.00-20-16 PR LUG

Dimensions: Wheel Base: Approx. 5385 mm

Overall length: Approx. 8330 mm

Overall width: Approx. 2490 mm

Overall height: Approx. 2985 mm

Vehicle weight: Approx. 11,180 kg

Max. Payload: Approx. 15,000 kg

Gross vehicle weight: Approx. 26,000 kg

Dump vessel: Inside length: 5,100 mm

Inside width: 2,300 mm

Inside height: 970 mm



Vessel volume: 11.3 m3
Thickness of deck plate: 6.0 mm
Thickness of side gate: 4.5 mm
Thickness of front plate: 4.5 mm
Thickness of sub frame: 6.0 mm

Main Construction: Pump Type - Gear type
Hoist - Single action type with link
Tipping performance:
Tipping angle: Approx 52 degrees
Lifting time: Approx 20 sec.
Lowering time: Approx 20 sec.

Including: 3-Point seat belt Air-conditioned
Air dryer Special chassis for dump
Fuel tank 200L Engine overrun buzzer
Long life coolant 30% Outside rear view mirrors
Reversing warning buzzer Power assisted transmission shift

